Boston Concord Yellow Jack

Tube: Nitrile (RMA Class A)
Reinforcement: Wire, 1, 2, or 3 Braid
Cover: Neoprene/Pinpricked MSHA Approved
Color: Yellow
Temperature Range: -40°F To +200°F
Type Of Branding: Impression
Working Pressure: 400-1500 PSI
Type Of Coupling: 430 'U' Series, Swaged/Crimped, Interlocking, or Steel Nipple. Clamps —Interlocking.
Branding: Boston Concord Yellow Jack Air

Features:
- Neoprene cover
- Nitrile tube (RMA Class A)
- Continuous permanent brand
- Wide range of sizes

Advantages:
- Abrasion, oil, and weather resistant
- Good oil resistance
- Easy identification
- Many applications

Markets:
- Construction Industry
- Oil Field Equipment
- Drilling Equipment
- Mining

Applications:
- Provide power to air-operated construction equipment. (Bull lines, jackhammer, etc.)
- Power air-operated drills, boring, and mining equipment

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H600808	1/2	12.7	1	31/32	24.6	40	1,500	50
H600808-100								100
H600808-150								150
H600812	3/4	19.1	1	1-1/4	31.8	62	1,200	50
H600812-100								100
H600812-150								150
H600816	1	25.4	1	1-1/2	38.1	80	1,000	50
H600816-100								100
H600816-150								150
H600820	1-1/4	31.8	1	1-13/16	46.0	122	650	50
H600820-100								100
H600820-150								150
H600824	1-1/2	38.1	2	2-1/8	53.9	143	600	50
H600824-100								100
H600824-150								150
H600832	2	50.8	2	2-21/32	67.4	216	600	50
H600832-100								100
H600832-150								150
H600840	2-1/2	63.5	2	3-5/32	80.1	240	400	50
H600840-100								100
H600840-150								150
H600848	3	76.2	2	3-23/32	94.4	310	400	50
H600848-100								100
H600848-150								150
H600864	4	101.6	3	5	127.0	579	400	50
H600864-100								100
H600864-150								150