

# Hose

## Dry Bulk Transfer

 Refer to warnings and safety information on pages 3-4 and page 66.

### Boston Lynx Softwall Dry Material



**Tube:** Natural Rubber/SBR Blend (3/16" tube thickness)  
Static Dissipating

**Reinforcement:** Fiber, 2 Spiral

**Cover:** SBR

**Color:** Black

**Temperature Range:** -10°F To +150°F

**Type Of Branding:** Printed Strip

**Working Pressure:** 50 PSI (Depending on coupling)

**Type Of Coupling:** Cam and Groove, or Combination Nipple. Clamps—Band.

#### Features:

- SBR cover
- Natural rubber/SBR blend tube 3/16" thick
- Conductive tube
- Continuous printed brand
- Available in longer lengths
- Soft wall hose

#### Advantages:

- Abrasion, age and weather resistant
- Static dissipating
- Easy identification
- Economical; less waste
- Folds flat for easy storage

#### Markets:

- Tank Truck
- In-plant Transfer
- Bottling Plant
- Coal Plant

#### Applications:

- Transfer of dry bulk (cement, sand, lime, etc.); discharge of any abrasive materials
- Transfer of bottle caps
- Transfer of cleaning agents

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	SPIRAL	NOMINAL O.D. (IN.) (MM)		APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
HQ31964-100	4	101.6	2	4-5/8	117.5	225	50	100