


# Hose

## Dry Bulk Transfer

 Refer to warnings and safety information on pages 3-4 and page 66.

### Boston Sabertooth Dry Material



**Tube:** Natural Rubber/SBR Blend  
Static Dissipating

**Reinforcement:** Fiber, 4 Spiral and Helical Wire

**Cover:** SBR

**Color:** Black

**Temperature Range:** -10°F To +160°F

**Type Of Branding:** Printed Strip

**Suction:** Full Vacuum

**Working Pressure:** 100 PSI (Depending on coupling)

**Type Of Coupling:** Cam and Groove, or Combination Nipple. Clamps—Band.

#### Features:

- SBR cover
- Natural rubber/SBR blend tube
- Conductive tube
- Continuous printed brand
- Available in longer lengths

#### Advantages:

- Abrasion, age and weather resistant
- Static dissipating
- Easy identification
- Economical; less waste

#### Markets:

- Tank Truck
- In-plant Transfer
- Bottling Plant
- Coal Plant

#### Applications:

- Transfer of dry bulk (cement, sand, lime, plastics, animal feed, etc.); suction/discharge of any abrasive materials
- Transfer of bottle caps
- Transfer of cleaning agents

PRODUCT NUMBER	NOMINAL I.D.		SPIRAL	NOMINAL O.D.		APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MIN. BEND RADIUS		STANDARD LENGTH (FT)
	(IN.)	(MM)		(IN.)	(MM)			(IN.)	(MM)	
H034748-100	3	76.2	4	4	101.6	320	100	9	228.6	100
H034764-100	4	101.6	4	5	127.0	440	100	11	279.4	100