



PowerClean™ Hose

Recommended For: Use on hot or cold water, high-pressure cleaning equipment. In 300' reels and 50' boxes.

Tube: Synthetic rubber specially compounded to handle high-pressure water service.

Reinforcement: High tensile steel one- or two-wire braid.

Cover: Specially compounded to handle pressure washer environment.

Temperature Range: -40°F to +250°F (-40°C to +121°C).

Couplings (see crimp manual for specifics):

MegaCrimp® Couplings, pages E13-51.



SPECIFICATIONS

Description	Part No. (50' Length)	Part No. (Bulk Reel)	Product No. (Bulk Reel)	Hose I.D. (In.)	Hose O.D. (In.)	Working Pressure (psi)	Min. Bend Radius (In.)	Bulk Reel Length (Ft.)
4PC3500	85720	70840	4657-2400	1/4	0.53	3,500	4.0	300
4PC6000	85721	70841	4657-2410	1/4	0.59	6,000	4.0	300
6PC3000	85722	70842	4657-2402	3/8	0.68	3,000	5.0	300
6PC3000 Blue	85723	70843	4657-2404	3/8	0.68	3,000	5.0	300
6PC3000 Yellow	85698	70848	4657-2417	3/8	0.68	3,000	5.0	300
6PC4000	85724	70844	4657-2225	3/8	0.68	4,000	5.0	300
6PC5000	85725	70845	4657-2407	3/8	0.74	5,000	5.0	300
8PC2500	85726	70846	4657-2408	1/2	0.80	2,500	7.0	300
8PC4000	85727	70847	4657-2426	1/2	0.86	4,000	7.0	300

NOTE: Not recommended for steam hose.