

CLEANING EQUIPMENT

GAUNTLET® 1500



- APPLICATION:** Goodyear Gauntlet® 1500 is for pressure washer equipment with working pressures up to 1500 psi. Its super abrasion-resistant cover provides maximum protection against adverse affects of oil and animal fats.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Black or Yellow oil-resistant Carbryn® synthetic rubber, RMA Class A (High Oil Resistance)
- REINFORCEMENT:** Braided (1) synthetic yarn up through 1/2". Braided (2) synthetic yarn for 3/4".
- TEMPERATURE:** -20°F to 200°F (-29°C to 93°C)
- PACKAGING:** 500' reel, maximum 3 pieces, 50' increments
- BRANDING:** Continuous brand "Goodyear" Gauntlet 1500 3/8" 1500 psi. Made in USA."
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Coupled lengths with MxMS fittings and Kink Guards available.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 536-480 (black) 536-474 (yellow)

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
1/4	6.4	0.59	15.0	1500	10.34	0.11	0.16
3/8	9.5	0.75	19.1	1500	10.34	0.18	0.27
1/2	12.7	0.84	21.3	1200	8.27	0.18	0.29
3/4	19.1	1.25	31.8	1500	10.34	0.41	0.61

Note: Not recommended for steam service.

Gauntlet 1500 in the 1/2" ID is rated at a working pressure of 1200 psi. All other sizes listed above are rated at a working pressure of 1500 psi.