



**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Shark®

(Specification 4686AR/4686DC)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1	25.4	1.45	36.8	150	1.03	30.0	762	5.0	127	.53	.24	100 ft.	X	4686-0701	\$8.53
1-1/4	31.8	1.71	43.4	150	1.03	30.0	762	6.0	152	.68	.31	100 ft.	X	4686-0702	9.42
1-1/2	38.1	1.96	49.8	150	1.03	30.0	762	8.0	203	.79	.36	100 ft.	X	4686-0703	10.28
2	50.8	2.46	62.5	150	1.03	30.0	762	10.0	254	1.01	.46	100 ft.	X	4686-0704	12.20
2	50.8	2.46	62.5	150	1.03	30.0	762	10.0	254	1.01	.46	200 ft.	400 ft.	4686-0710	12.20
2-1/2	63.5	3.02	76.7	150	1.03	30.0	762	12.0	305	1.46	.66	100 ft.	X	4686-0705	15.94
3	76.2	3.58	90.9	150	1.03	30.0	762	15.0	381	2.01	.91	100 ft.	X	4686-0706	18.63
4	101.6	4.58	116.3	150	1.03	30.0	762	20.0	508	2.62	1.19	100 ft.	X	4686-0707	26.48
5	127.0	5.60	142.2	100	.69	30.0	762	25.0	635	3.89	1.76	100 ft.	X	4686-0708	41.23
6	152.4	6.65	168.9	100	.69	30.0	762	30.0	762	4.84	2.20	20 ft.	X	4686-0711	52.24
6	152.4	6.65	168.9	100	.69	30.0	762	30.0	762	4.84	2.20	25 ft.	X	4686-0712	52.24
6	152.4	6.65	168.9	100	.69	30.0	762	30.0	762	4.84	2.20	100 ft.	X	4686-0709	52.24

RECOMMENDED FOR: Suction hose used to convey water, detergents, phosphate ester hydraulic fluids and dilute solutions of acids, alkalis and glycols.

TEMPERATURE: -40°F to +180°F (-40°C to +82°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile with steel wire helix.
Cover: Type D (SBR). Black with green spiral stripe.

COUPLINGS: (See Coupling Section on page 122 for maximum rated working pressure.) Reference pages 122-133.

PACKAGING: All lengths coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: Shark® Water Suction/Discharge 150 PSI (1.03MPa) WP Made In U.S.A.”

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" and 200 feet for sizes above 4". If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Barracuda®

(Specification 4686AT)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack			
1	25.4	1.33	33.8	150	1.03	30.0	762	5.0	127	.39	.18	100 ft.	400 ft.	4686-0199	\$5.50
1-1/4	31.8	1.61	40.9	150	1.03	30.0	762	5.0	127	.51	.23	100 ft.	X	4686-0203	6.00
1-1/2	38.1	1.86	47.2	150	1.03	30.0	762	6.0	152	.60	.27	100 ft.	X	4686-0204	7.25
1-1/2	38.1	1.86	47.2	150	1.03	30.0	762	6.0	152	.60	.27	200 ft.	400 ft.	4686-0237	7.25
2	50.8	2.36	59.9	150	1.03	30.0	762	8.0	203	.76	.35	100 ft.	X	4686-0200	8.40
2	50.8	2.36	59.9	150	1.03	30.0	762	8.0	203	.76	.35	200 ft.	400 ft.	4686-0235	8.40
2-1/2	63.5	2.96	75.2	150	1.03	30.0	762	10.0	254	1.06	.48	100 ft.	X	4686-0205	10.40
3	76.2	3.54	89.9	150	1.03	30.0	762	14.0	356	1.74	.79	100 ft.	X	4686-0201	11.60
3	76.2	3.54	89.9	150	1.03	30.0	762	14.0	356	1.74	.79	200 ft.	400 ft.	4686-0236	11.60
4	101.6	4.54	115.3	150	1.03	30.0	762	18.0	457	2.25	1.02	100 ft.	X	4686-0202	16.50
4	101.6	4.54	115.3	150	1.03	30.0	762	18.0	457	2.25	1.02	200 ft.	400 ft.	4686-0208	16.50
6	152.0	6.68	170.0	100	.69	30.0	762	28.0	711	3.94	1.79	20 ft.	X	4686-0207	43.15
6	152.0	6.68	170.0	100	.69	30.0	762	28.0	711	3.94	1.79	25 ft.	X	4686-0206	43.15
6	152.0	6.68	170.0	100	.69	30.0	762	28.0	711	3.94	1.79	100 ft.	400 ft.	4686-0234	43.15
8	203.2	9.00	228.6	100	.69	30.0	762	40.0	1016	8.81	4.00	25 ft.	X	4686-0209	110.20
10	254.0	11.27	286.3	100	.69	30.0	762	50.0	1270	15.80	7.17	25 ft.	X	4686-0210	179.29
12	304.8	13.27	337.1	100	.69	30.0	762	60.0	1524	18.63	8.45	25 ft.	X	4686-0211	205.07

RECOMMENDED FOR: Medium to light duty water suction/discharge for agricultural, construction and industrial applications. EPDM tube designed to handle a variety of liquids including Lasso*, Lasso II* and Freedom*. Recommended for sanitation lines in marine applications.

TEMPERATURE: -40°F to +180°F (-40°C to +82°C). For 1" through 6" sizes.
-32°F to +200°F (-36°C to +93°C). For 8" through 12" sizes.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile with steel wire helix.
Cover: Type B₂ (Specially compounded elastomer for ozone and abrasion resistance). Black with green spiral stripe. For sizes 1" through 6" sizes
Type P (EPDM). Black with green spiral stripe. For sizes 8", 10" and 12" only.

COUPLINGS: [5], [6], [7], [8] or [49], all sizes. Reference pages 122-133.

PACKAGING: 1" through 6": Packaged with each length coiled and wrapped in polyethylene.
8" through 12": Packaged with each length in nylon woven fabric.

BRANDING: Continuous transfer label. Example: Barracuda® Water Suction/Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" I.D. and 200 feet for sizes above 4" I.D. If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

* Registered trademarks of Monsanto.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.





**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Steelhead®

(Specification 3135SP)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack			
1-1/2	38.1	1.98	50.3	150	1.03	—	—	12.0	305	.70	.32	100 ft.	X	3135-2651	\$11.08
1-5/8	41.3	2.10	53.3	150	1.03	—	—	15.0	381	.74	.34	100 ft.	400 ft.	3135-2652	11.55
1-7/8	47.6	2.35	59.7	150	1.03	—	—	15.0	381	.88	.40	100 ft.	400 ft.	3135-2653	12.53
2	50.8	2.48	63.5	150	1.03	—	—	20.0	508	.93	.42	100 ft.	X	3135-2654	13.21
2-1/2	63.5	2.99	76.0	150	1.03	—	—	25.0	635	1.14	.52	100 ft.	X	3135-2655	16.50
3	76.2	3.49	88.7	150	1.03	—	—	36.0	914	1.35	.61	100 ft.	X	3135-2656	20.62
3	76.2	3.49	88.7	150	1.03	—	—	36.0	914	1.35	.61	200 ft.	400 ft.	3135-2661	20.62
3-1/2	88.9	3.99	101.4	150	1.03	—	—	42.0	1067	1.64	.74	100 ft.	400 ft.	3135-2657	21.18
4	101.6	4.49	114.1	150	1.03	—	—	47.6	1219	1.85	.84	100 ft.	X	3135-2658	28.81
4-1/2	114.3	5.01	127.3	150	1.03	—	—	54.0	1372	2.16	.98	100 ft.	X	3135-2659	30.25
6	152.4	6.51	165.4	150	1.03	—	—	72.0	1829	2.84	1.29	100 ft.	X	3135-2660	54.45

RECOMMENDED FOR: Water discharge in heavy duty industrial applications.

TEMPERATURE: -40°F to +150°F (-40°C to +66°C) continuous service.

CONSTRUCTION: **Tube:** Type D (SBR). Black.
Reinforcement: Multiple plies of synthetic, high tensile textile.
Cover: Type D (SBR). Black with green spiral stripe.

COUPLINGS: 1, 3, 5, or 7. Reference pages 122-133.

PACKAGING: 100' coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: Steelhead® HD Water Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" and 200 feet for sizes above 4". If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Marlin®

(Specification 3137M)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack			
1-1/2	38.1	1.82	46.2	150	1.03	—	—	12.0	305	.47	.21	100 ft.	X	3137-0370	\$6.54
1-1/2	38.1	1.90	48.3	150	1.03	—	—	12.0	305	.63	.29	100 ft.	X	3137-0371	8.74
2	50.8	2.33	59.2	150	1.03	—	—	20.0	508	.65	.30	100 ft.	X	3137-0372	7.20
2	50.8	2.41	61.2	150	1.03	—	—	20.0	508	.84	.38	100 ft.	X	3137-0373	9.72
2-1/2	63.5	2.83	71.9	150	1.03	—	—	25.0	635	.80	.36	100 ft.	400 ft.	3137-0374	10.14
2-1/2	63.5	2.91	73.9	150	1.03	—	—	25.0	635	1.02	.46	100 ft.	X	3137-0375	13.98
3	76.2	3.33	84.6	150	1.03	—	—	36.0	914	.95	.43	100 ft.	X	3137-0376	10.17
3	76.2	3.41	86.6	150	1.03	—	—	36.0	914	1.21	.55	100 ft.	X	3137-0377	16.22
3-1/2	88.9	3.91	99.3	150	1.03	—	—	42.0	1067	1.47	.67	100 ft.	X	3137-0378	20.50
4	101.6	4.33	110.0	150	1.03	—	—	47.6	1219	1.32	.60	100 ft.	X	3137-0379	12.81
4	101.6	4.33	110.0	150	1.03	—	—	47.6	1219	1.32	.60	200 ft.	400 ft.	3137-1272	12.81
4	101.6	4.41	112.0	150	1.03	—	—	47.6	1219	1.67	.76	100 ft.	X	3137-0380	24.12
5	127.0	5.44	138.2	150	1.03	—	—	60.0	1524	2.17	.98	100 ft.	X	3137-0381	29.82
6	152.4	6.40	162.6	150	1.03	—	—	72.0	1829	2.32	1.05	100 ft.	X	3137-0382	35.57
6	152.4	6.49	164.9	150	1.03	—	—	72.0	1829	2.96	1.34	100 ft.	X	3137-0383	49.79

RECOMMENDED FOR: Water discharge in heavy duty service requiring a compact, rugged and lightweight hose.

TEMPERATURE: -40°F to +180°F (-40°C to +82°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Multiple plies of synthetic, high tensile textile.
Cover: Type D (SBR). Black with green spiral stripe.

COUPLINGS: . Reference pages 122-133.

PACKAGING: 100' coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: Marlin® Water Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" and 200 feet for sizes above 4". If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.





**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Dolphin®

(Specification 3137T)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1-1/4	31.8	1.53	38.9	150	1.03	—	—	—	—	.37	.17	100 ft.	X	3137-0884	\$5.35
1-1/2	38.1	1.78	45.2	150	1.03	—	—	—	—	.43	.20	100 ft.	X	3137-0883	5.85
1-1/2	38.1	1.78	45.2	150	1.03	—	—	—	—	.43	.20	200 ft.	X	3137-0898	5.85
2	50.8	2.32	58.9	150	1.03	—	—	—	—	.65	.30	100 ft.	X	3137-0885	6.50
2	50.8	2.32	58.9	150	1.03	—	—	—	—	.65	.30	200 ft.	X	3137-0905	6.50
2-1/2	63.5	2.82	71.6	150	1.03	—	—	—	—	.80	.36	100 ft.	X	3137-0888	8.45
3	76.2	3.36	85.3	150	1.03	—	—	—	—	1.08	.49	100 ft.	X	3137-0886	8.45
3	76.2	3.36	85.3	150	1.03	—	—	—	—	1.08	.49	200 ft.	X	3137-0895	9.50
4	101.6	4.36	111.7	150	1.03	—	—	—	—	1.41	.64	100 ft.	X	3137-0889	12.55
4	101.6	4.36	111.7	150	1.03	—	—	—	—	1.41	.64	200 ft.	X	3137-0896	12.55
6	152.4	6.38	162.1	125	.86	—	—	—	—	2.09	.95	100 ft.	X	3137-0890	22.20
6	152.4	6.38	162.1	125	.86	—	—	—	—	2.09	.95	200 ft.	X	3137-0892	22.20

RECOMMENDED FOR: Medium to light duty water discharge for agricultural, construction and industrial applications. EPDM tube designed to handle a variety of liquids including Lasso*, Lasso II* and Freedom*.

TEMPERATURE: -40°F to +180°F (-40°C to +82°C).

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile.
Cover: Type P (EPDM). Black with green spiral stripe.

COUPLINGS: [5], [6], [7], [8] or [49], all sizes. Reference pages 122-133.

NOTE: 3:1 Safety Factor for Burst Pressure to Working Pressure is reduced when the temperature increases.

PACKAGING: 100' length coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: Dolphin® Water Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" I.D. and 200 feet for sizes above 4" I.D. If a special transfer label is required, contact Denver Industrial Hose Marketing for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Denver Industrial Hose Marketing for pricing, order requirements and availability.

* Registered trademarks of Monsanto.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



Water Hose

Master-Flex® 500

(Specification 7744)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack			
1-1/2	38.1	1.67	42.4	75	.52	—	—	—	—	.17	.08	300 ft.	X	7744-1001	\$1.32
2	50.8	2.16	54.9	65	.45	—	—	—	—	.21	.10	300 ft.	X	7744-1002	1.61
2-1/2	63.5	2.55	64.8	60	.41	—	—	—	—	.28	.13	300 ft.	X	7744-1003	2.30
3	76.2	3.17	80.5	60	.41	—	—	—	—	.39	.18	300 ft.	X	7744-1004	2.71
4	101.6	4.20	106.7	60	.41	—	—	—	—	.53	.24	300 ft.	X	7744-1005	3.63
6	152.4	6.20	157.5	45	.31	—	—	—	—	.88	.40	300 ft.	X	7744-1006	6.05
8	203.2	8.16	207.3	45	.31	—	—	—	—	1.27	.58	300 ft.	X	7744-1007	12.10

RECOMMENDED FOR: General lay flat water discharge service. Excellent for job sites in construction, irrigation and areas where a lightweight, flexible hose is required.

TEMPERATURE: +25°F to +120°F (-4°C to +49°C) continuous service.

CONSTRUCTION: **Tube:** Type G (PVC). Blue with yellow identification
Reinforcement: Synthetic, high tensile textile.

COUPLINGS: 5, 6, 7 or 49. One band for 1-1/2". Two bands for 2" I.D. and larger. Reference pages 122-133.

PACKAGING: 300' length coiled in polyethylene and banded, one length.

BRANDING: Ink stamp every 5 ft. with I.D. only.

SPECIAL ORDER REQUIREMENTS: None.

REMNANT LENGTHS: None.





**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Master-Flex® 100GR

(Specification 7744)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack			
1	25.4	1.27	32.3	90	.62	28.0	711	3.0	76	.27	.12	100 ft.	X	7744-3101	\$2.54
1-1/4	31.8	1.53	38.9	90	.62	28.0	711	4.0	102	.36	.16	100 ft.	X	7744-3102	3.31
1-1/2	38.1	1.82	46.2	90	.62	28.0	711	5.0	127	.47	.21	100 ft.	X	7744-3103	3.76
2	50.8	2.36	59.9	70	.48	28.0	711	6.0	152	.66	.30	100 ft.	X	7744-3104	5.44
2-1/2	63.5	2.90	73.7	65	.45	28.0	711	8.0	203	.92	.42	100 ft.	X	7744-3105	8.56
3	76.2	3.44	87.4	60	.41	28.0	711	9.0	229	1.20	.54	100 ft.	X	7744-3106	10.31
4	101.6	4.52	114.8	50	.34	28.0	711	13.0	330	1.87	.86	100 ft.	X	7744-3107	17.20
5	127.0	5.65	143.5	45	.31	28.0	711	21.0	533	3.08	1.40	100 ft.	1,000 ft.	7744-3108	24.88
6	152.4	6.80	172.7	45	.31	28.0	711	24.0	610	4.56	2.07	100 ft.	X	7744-3109	32.46

*Working pressure and suction at +72°F (+22°C).

RECOMMENDED FOR: Conveying water and light chemical solutions under suction or rated discharge pressure.

TEMPERATURE: -10°F to +130°F (-23°C to +55°C) continuous service.

CONSTRUCTION: **Tube:** Type G (PVC). Green.

Reinforcement: Rigid thermoplastic helix.

COUPLINGS: [1], [6], [7] or [49], all sizes. Reference pages 122-133.

PACKAGING: All lengths coiled and wrapped in polyethylene.

BRANDING: Unlabeled.

SPECIAL ORDER

REQUIREMENTS: Special production runs require minimum order quantities of 1,000 feet per size. No deviations allowed to above product.

REMNANT LENGTHS: None.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.



**Industrial Hose
Products/List Prices**



39496-000
July 30, 2007
Supersedes 39496-000
July 1, 2006

Water Hose

Master-Flex® 101CL

(Specification 7744)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1	25.4	1.29	32.8	100	.69	28.0	711	3.0	76	.27	.12	100 ft.	X	7744-2101	\$2.44
1-1/4	31.8	1.56	39.6	90	.62	28.0	711	4.0	102	.34	.15	100 ft.	X	7744-2102	3.47
1-1/2	38.1	1.84	46.7	90	.62	28.0	711	4.0	102	.47	.21	100 ft.	X	7744-2103	3.73
2	50.8	2.39	60.7	70	.48	28.0	711	5.0	127	.66	.30	100 ft.	X	7744-2104	5.22
2-1/2	63.5	2.92	74.2	65	.45	28.0	711	7.0	178	.92	.42	100 ft.	X	7744-2105	7.13
3	76.2	3.46	87.9	55	.38	28.0	711	8.0	203	1.20	.54	100 ft.	X	7744-2106	8.97
4	101.6	4.56	115.8	50	.34	28.0	711	12.0	305	1.87	.85	100 ft.	X	7744-2107	12.89
5	127.0	5.65	143.5	45	.31	28.0	711	21.0	533	3.00	1.36	100 ft.	1,000 ft.	7744-2108	23.52
6	152.4	6.80	172.7	45	.31	28.0	711	23.0	584	4.42	2.00	100 ft.	X	7744-2109	27.14

*Working pressure and suction at +72°F (+22°C).

RECOMMENDED FOR: Conveying water and light chemical solutions where a clear PVC hose with a white helix is desirable for heavy duty applications.

TEMPERATURE: -10°F to +130°F (-23°C to +55°C) continuous service.

CONSTRUCTION: **Tube:** Type G (PVC). Clear.

Reinforcement: Rigid thermoplastic helix.

COUPLINGS: 1, 6, 7 or 49, all sizes. Reference pages 122-133.

PACKAGING: All lengths coiled and wrapped in polyethylene.

BRANDING: Unlabeled.

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 1,000 feet per size. No deviations allowed to above product.

REMNANT LENGTHS: None.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.

