

# Sand Blast Hose Couplings

Construction



**Quick Disconnect Ends**  
(Supplied with Phillips Head Screws)



**External Nozzle Holders**  
(Supplied with Phillips Head Screws)

## Aluminum Sand Blast Hose Couplings — Quick Disconnect Ends

Part Number	Hose Size	Hose OD	Weight Std. Ctn.	Standard Carton*
★ Q-AL050	1/2"	1.06"	0.15	6
Q-AL1	3/4"	1 1/2"	0.36	6
Q-AL2	1"	1 7/8"	0.36	6
Q-AL3	1 1/4"	2 5/32"	0.66	6
Q-AL4	1 1/2"	2 3/8"	0.88	6
Q-AL5 ‡	1 1/2"	2 3/8"	1.10	6

★ To be used on 1.06" OD Hose only.

## Brass Sand Blast Hose Couplings — Quick Disconnect Ends

Part Number	Hose Size	Hose OD	Weight Std. Ctn.	Standard Carton*
Q-BR1	3/4"	1 1/2"	1.06	6
Q-BR2	1"	1 7/8"	1.12	6
Q-BR3	1 1/4"	2 5/32"	1.94	6
Q-BR4	1 1/2"	2 3/8"	2.64	6
Q-BR5 ‡	1 1/2"	2 3/8"	3.50	6

## Plated Iron Sand Blast Hose Couplings — Quick Disconnect Ends

Part Number	Hose Size	Hose OD	Weight Std. Ctn.	Standard Carton*
Q-PI1	3/4"	1 1/2"	0.98	10
Q-PI2	1"	1 7/8"	1.02	10
Q-PI3	1 1/4"	2 5/32"	1.84	10
Q-PI4	1 1/2"	2 3/8"	2.38	10

## Natural Rubber Gaskets for Sand Blast Hose Couplings



Part Number	Weight Each	Standard Package*
SBG	0.24	10
SRG-2 ‡	0.63	10

‡ NOTE QAL5, QBR5, SB-3AL, and SBBR3 are large ID full-flow fittings for 1 1/2" ID hose and are not interchangeable with standard fittings. Full-flow fittings require SRG-2 gaskets.

## Aluminum Sand Blast Hose Couplings — External Nozzle Holders with Female NPS Thread

Part Number	Hose Size	Hose OD	NPS Female Thread Size	Weight Std. Ctn.	Std.* Ctn.
★ NH-AL050	1/2"	1.06"	3/4"	0.15	6
NH-AL1	3/4"	1 1/2"	1 1/4"	0.30	6
NH-AL2	1"	1 7/8"	1 1/4"	0.36	6
NH-AL3	1 1/4"	2 5/32"	1 1/4"	0.52	6
NH-AL4	1 1/2"	2 3/8"	1 1/4"	0.98	6

★ To be used on 1.06" OD Hose only.

## Brass Sand Blast Hose Couplings — External Nozzle Holders

Part Number	Hose Size	Hose OD	NPS Female Thread Size	Weight Std. Ctn.	Std.* Ctn.
NH-BR1	3/4"	1 1/2"	1 1/4"	0.94	6
NH-BR2	1"	1 7/8"	1 1/4"	1.02	6
NH-BR3	1 1/4"	2 5/32"	1 1/4"	1.58	6
NH-BR4	1 1/2"	2 3/8"	1 1/4"	2.96	6

## Sand Blast Quick Disconnect Couplings x Female NPT

## Aluminum Quick Disconnect Female Threaded Adapters — NPT



Part Number	Hose Size	NPT Female Thread Size	Weight Std. Ctn.	Std.* Ctn.
SB-AL1	1 1/4"	1 1/4"	0.34	6
SB-AL2	1 1/2"	1 1/4"	0.28	6
SB-AL3 ‡	1 1/2"	1 1/4"	1.05	6

## Brass Quick Disconnect Female Threaded Adapters — NPT

Part Number	Hose Size	NPT Female Thread Size	Weight Std. Ctn.	Std.* Ctn.
SB-BR1	1 1/4"	1 1/4"	1.02	6
SB-BR2	1 1/2"	1 1/4"	0.84	6
SB-BR3 ‡	1 1/2"	1 1/4"	3.05	6

## Universal Carbon Steel Safety Clips and Lanyards — For use with all Universal Air Hose and Sandblast Couplings

Part Number	Weight Std. Pkg.	Std.* Pkg.
USCL	.25 lbs	10



**\*All couplings, clamps, gaskets, safety clips and lanyards sold in full standard packages only.**

**All prices and specifications subject to change without notice.**