

 Refer to warnings and safety information on pages 3-4 and pages 115-118

**Boston Concord Standard Steam & Concord Standard Steam-Spiral Stripe**



**Tube:** Patrex (Chlorobutyl)  
**Reinforcement:** Wire, 2 Braid, 2 Stainless Steel Static Wires  
**Cover:** EPDM/Pinpricked  
**Color:** Black (BK), Black and Red Stripe (RD)  
**Temperature Range:** +450°F  
**Type Of Branding:** Impression  
**Working Pressure:** 250 PSI (Depending on coupling)  
 10:1 Safety Factor  
**Type Of Coupling:** Interlocking.  
 Clamps—Interlocking, (2 Bolt, 4 Bolt).

**Features:**

- EPDM cover
- Patrex (Chlorobutyl) tube
- Continuous impression brand and date code
- Minimum 10-to-1 safety factor
- Built in separate static wire
- Barber pole striped cover (RD)

**Advantages:**

- Heat, age, ozone and weather resistant.
- Excellent heat resistance
- Handles most steam cleaning detergents
- Easy identification
- Safety & maintenance records
- Meets safety standards of RMA
- Assures safe grounding
- Safety
- Color code system

**Markets:**

- Chemical/Petroleum Industry
- Industrial Cleaning Markets
- Ship Building
- Lumber/Woodworking
- Plywood Mfg./Cardboard
- Pulp Processing

**Applications:**

- Transfer of steam for processing products and cleaning equipment
- Transfer of steam or hot 200°F detergent-type solutions for cleaning of equipment, tanks, buildings, etc.
- Transfer of steam to melt glues, waxes, etc.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT	MAXIMUM WORKING PRESS. (PSI)	STANDARD LENGTH (FT)*
H008408	1/2	12.7	2	1-1/8	28.6	55	250	50(BK,RD)
H008412	3/4	19.1	2	1-3/8	34.9	78	250	50(BK,RD)
H008416	1	25.4	2	1-5/8	41.3	100	250	50(BK,RD)
H008420	1-1/4	31.8	2	1-15/16	49.2	135	250	50(BK,RD)
H008424	1-1/2	38.1	2	2-3/16	55.6	155	250	50(BK,RD)
H008432	2	50.8	2	2-11/16	68.3	194	250	50(BK,RD)

*Not to be used as a pressure washer hose*

*\* 225 - 295 foot reels available as Made to Order*